



SPCP181808G

| | |
|--------------|---|
| Navn: | Cubo S-kapsling |
| | Size 175 x 175 x 75 mm, 50 mm base, plain sides, grey cover, PC |
| Type: | SPCP181808G |
| GTIN: | 6418677155628 |
| El-nummer: | 2509751 |
| Beskrivelse: | Ensto Cubo S is a series of small to medium size enclosures available with knockouts or plain sides. The base of the enclosures is equipped with unique slots for printed circuit boards. |
| Pakke: | 1/7 |
| Enhet: | STK |



Teknisk spesifikasjon

Innhold Kapslingsbase, deksel, dekselskruer, monteringskruer

Rangeringer

Nivå på beskyttelse IP66/IP67
Brann klasse UL 746 C 5V
ETIM Enclosure/switchgear cabinet (empty)

Mekanisk

Mekanisk styrke IK 08

Dimensjoner

Høyde 175 mm
Bredde 175 mm
Dybde 75 mm
Vekt 0.46 kg
Volum 229.69 cm³
Indre dybde 60.5 mm
Underdelen ytre dybde 50 mm
Lokkets ytterhøyde 25 mm
Størrelse 175 x 175 x 75

Temperaturer

Driftstemperatur -40 ... 80 °C
Kortsiktig temperaturområde -40 ... 120 °C

Materialer

Underdel Fiberglassarmert polykarbonat
Lokk Polykarbonat
Lokkskruvar Polyamid



Saves Your Energy

PRODUKTKORT/FDV

12.5.2016

2/2

SPCP181808G

| | |
|-----------------------------|------------------|
| Lokketetning | Polyuretan |
| Farger | |
| Farge | Grå |
| Sertifikater | |
| Standarder | EN 62208, GOST R |
| ETIM | |
| Width | 175 mm |
| Height | 175 mm |
| Depth | 75 mm |
| Material | Plastic |
| Type of surface | Untreated |
| Colour | Grey |
| RAL-number | 7035 |
| Wall fastening possible | x |
| Suitable for outdoor set-up | x |
| Impact strength | IK08 |
| Degree of protection (IP) | IP67 |