

WATER PRESSURE TRANSMITTER VPL 60

Water pressure transmitter VPL 60 is designed to detect pressures at the HVAC applications; water, heating, air-conditioning and refrigeration systems.

Outputs (0-10Vdc or 4-20mA) are directly proportional to the pressure inside the pipeline.

Pressure sensor element is made by using ceramic techniques. Allowed mediums are water, air, oils and glycol/water mixtures. Material of wetted parts is stainless steel (AISI 303) and housing for electrical connections is made of heat resisting plastics.

When the transmitter is connected to the cold / chilled water circuit, condensation on the sensor must be prevented.

The process connection is made by a thread of R1/2".

The range for measuring can be chosen at commissioning.

The socket for display is ready installed on the board. The cover with display can be added afterwards.

ATTENTION! Device may be damaged by overpressure if installation is made against fluid and closed valve.



Technical data:

Supply 24 Vac / dc, 1VA Range 0...16 bar (to choose at commissioning) 0...25 bar 0...40 bar Mounting Outputs Inaccuracy Temperature drifting Long term stability Operating conditions humidity temperature Allowed medium temp. Max. overpressure Protection class

Tool Material

wetting parts housing

wiring:	
1	24 Vac / dc
2	0V
3	010 Vdc
4	420 mA

0...60 bar R 1/3' 0...10 Vdc, < 2 mA 4...20 mA, < 800 Ω < +/ - 0,5 bar < +/ - 0,3 bar / 10K < +/ - 0,3 bar / year non-condensing 0...+60 °C 0...+85 °C 120 bar IP 54, cable gland or sensor down 27 mm

AISI 303 (stainless), ceramics heat resisting plastic

Wiring

1	24 Vac / dc
2	0V
3	010 Vdc
4	420 mA

Ordering guide:

Model	Product number	Description
VPL 60	1134030	water press. transmitter range 0-16, 0-25, 0-40 or 0-60 bar
VPL 60-N	1134310	transmitter with display

Products fulfill the requirements of directive 2004/108/EY and are in accordance with the standards EN61000-6-3 (Emission) and EN61000-6-2 (Immunity).

Produal Oy

Keltakalliontie 18 48770 Kotka FINLAND www.produal.com

Tel: +358-5-230 9200 Fax: +358-5-230 9210 info@produal.fi